



**GUARDIAN**  
BUILDING PRODUCTS



# ATTIC

**NO  
MACHINE  
REQUIRED  
EASY TO INSTALL**

# INSULATION



1. Open bag with utility knife.



2. Rake to desired thickness using a garden or leaf rake.



3. Measure thickness. See chart for thermal performance.

## COVERAGE INFORMATION

THERMAL RESISTANCE		MAXIMUM COVERAGE PER BAG		MINIMUM WEIGHT PER BAG.		INITIAL INSTALLED THICKNESS	
R	RSI	sq. ft.	m <sup>2</sup>	lbs./sq. ft.	Kg/m <sup>2</sup>	inches	mm
38	6.7	38.3	3.6	0.89	4.3	14.0	355
30	5.3	47.0	4.4	0.72	3.5	11.0	279
25	4.4	52.8	4.9	0.64	3.1	9.0	228
19	3.3	61.5	5.7	0.55	2.7	6.0	152
13	2.3	69.0	6.4	0.49	2.4	3.5	89

Nominal bag weight 35 lb. (15.9 Kg)



# **ATTIC INSULATION**



## DESCRIPTION

Guardian's ATTIC INSULATION is yellow, loose-fill fiberglass insulation.

- Non-Corrosive
- Non-Flammable
- Non-Combustible
- Pest Resistant
- 35% Recycled Product

## APPLICATION

Guardian's ATTIC INSULATION is a loose-fill insulation installed without a machine. It is a "do-it-yourself" product that is installed manually, using a household garden or leaf rake or some other long-handled tool (such as a hoe, pitchfork, etc.) that enables the person to "fluff and spread" the loose-fill insulation. The product is installed by "spreading" the insulation over an area to a specified thickness to achieve the desired thermal value. It is not suitable for exposed applications. Insulation should not be installed over eave vents or near light fixtures or other heat generating devices.

## PACKAGING

- 35 lbs (15.9 Kg) nominal bag weight
- 1050 bags per 53' truck
- Load factor: 0.102% of 53' truck.

## SPECIFICATIONS

This product meets or exceeds the requirements of:

- ASTM C 764, Type II
- ATM C 518 and C 687 - Thermal Resistance (R-value)
- ASTM 136 - Combustion Characteristics  
Flame Spread 5, Smoke Developed 5



**GUARDIAN**  
**BUILDING PRODUCTS**  
FIBERGLASS INSULATION

1000 EAST NORTH STREET, ALBION, MI 49224  
1-800-748-0035  
WWW.GUARDIANBP.COM