



Manufacturer:
GUARDIAN
 BUILDING PRODUCTS
 FIBERGLASS INSULATION



1000 East North Street
 Albion, MI 49224

INSULATION CERTIFICATE



ATTIC GUARD® OPEN ATTIC COVERAGE INFORMATION

R-VALUE*	BAGS PER 1000 SQ. FT.	MAXIMUM NET COVERAGE	MINIMUM WEIGHT PER SQ. FT.	INITIAL INSTALLED THICKNESS	MINIMUM SETTLED THICKNESS
R-60	40.00	25 SF	1.105 LBS	21.50"	21.50"
R-49	31.25	32 SF	0.865 LBS	18.00"	18.00"
R-44	27.77	36 SF	0.771 LBS	16.25"	16.25"
R-38	23.25	43 SF	0.659 LBS	14.25"	14.25"
R-30	17.85	56 SF	0.504 LBS	11.50"	11.50"
R-26	15.62	64 SF	0.436 LBS	10.25"	10.25"
R-22	12.98	77 SF	0.362 LBS	9.00"	9.00"
R-19	10.98	91 SF	0.307 LBS	8.00"	8.00"
R-13	7.57	132 SF	0.213 LBS	5.50"	5.50"
R-11	6.49	154 SF	0.181 LBS	4.75"	4.75"

*R means resistance to heat flow. The higher the R-value, the greater the insulating power. Ask your seller for the fact sheet on R-values.
 Bag Weight: nominal 28 LBS., minimum 26 LBS. For pneumatic application only. Not for exposed applications. Insulation should not be installed over eave vents. Thermal resistance values are determined in accordance with ASTM C 687 and ASTM C 518. This product meets or exceeds the requirements of ASTM C 764 Type 1.

Builder's and Applicator's Certification Signature

This is to certify the insulation has been installed in conformity with the requirements indicated on this card to provide thermal resistance value of R _____ using _____ bags of insulation to cover _____ square feet area.

Depth of previous insulation _____, R _____. Type of insulation: _____ Upgrade New Construction
Inches R-value Mineral Wool, Fiberglass, Etc.

 Date Company Name (Builder) Address Phone Builder's Signature

 Date Company Name (Applicator) Address Phone Applicator's Signature