

Manufactured By
GUARDIAN FIBERGLASS INSULATION
 1000 East North Street
 Albion, MI 49224

ASURE[®]R PLUS

Spray-On
Insulation
System

AsureR PLUS technology is covered by one or more of the following U.S. Patents.
 5,641,368 5,947,646 6,047,518 6,262,164
 5,666,780 5,952,418 6,012,263
 5,921,055 5,984,590 6,045,298
 as well as certain foreign patents.



Insulation Certification

This document certifies that **AsureR PLUS** fiberglass insulation has been installed using the **AsureR System** at _____ on ____/____/____ in conformance with the requirements indicated on the chart below.

Street Address, State Date

SIDEWALL COVERAGE INFORMATION

Nominal R-value	Thickness	Density	Bags Per 1000 Square Feet	Minimum Weight Per Square Foot	Maximum Coverage Per Bag
To obtain a thermal resistance (R) of:	Installed Insulation should not be less than: (inches)	Pounds per Ft ³	Bags per 1000 Ft ² of Net Area:	Pounds per Ft ²	Contents of Bag should not cover more than: (Ft ²)
R-14	3.50 (2x4)	1.9	17.5	0.55	57
R-22	5.50 (2x6)	1.9	27.5	0.87	36
R-29	7.25 (2x8)	1.9	36.2	1.15	28
R-37	9.25 (2x10)	1.9	46.2	1.46	22
R-15	3.50 (2x4)	2.2	21.5	0.64	47
R-23	5.50 (2x6)	2.2	33.7	1.01	30
R-31	7.25 (2x8)	2.2	44.4	1.33	23
R-39	9.25 (2x10)	2.2	56.7	1.70	18

Nominal bag weight 32 lbs. For pneumatic application only. Thermal resistance values are determined in accordance with ASTM C 518. This product meets or exceeds the requirements of ICC ES-5437, ASTM C 1014-03, ASTM C 764, CCMC 13315-R.

Builder's and Applicator's Certification Signature

AsureR PLUS fiberglass insulation has been installed into the wall cavities to provide thermal resistance of R _____ using _____ bags to cover _____ sq. ft. area. New construction Upgrade

Date Company Name (Builder) Address Phone Builder's Signature

Date Company Name (Applicator) Address Phone Applicator's Signature